TECHNICAL SPECIFICATIONS OF VISHWAKARMA BRAND UPPER FEEDING CUTTER THRESHER

TIN NO. 08102150260

VISHWAKARMA

MOB.: +91-9829211777 +91-9460635977 +91-9928509209

AGRO INDUSTRIES

MANUFECTURER & SUPPLYER OF ALL KIND AGRICULTURE EQUIPMENTS



G-181(A) UDHYOG VIHAR JAITPURA, TEH.:CHOMU,
DISTT.:JAIPUR (RAJASTHAN),PIN- 303704
PH. NO.: 01423-220777(O), 01423-224381
Website.: www.vishwakarmaagroindustries.com,
www.vishwakarmaagro.in

Email.:vishwakarmaagro777@gmail.com
AN ISO 9001-2008 CERTIFIED COMPANY



AWARD AND ACHIEVEMENTS

- **A RASTRIYA UDHYOG RATNA AWARD 2013**
- **❖ QUALITY BRAND AWARD 2013**
- **❖ RAJIV GANDHI UDHYOG GOURAV AWARD 2013**
- ❖ CUTTER THRESHER TESTED AND APPROVED BY MAHARANA PRATAP AGRICULTURE UNIVERSITY, UDAYPUR (RAJASTHAN) TESTING REPORT NO.: CTATE/FMTC/2012/34

S.N.	TCHNICAL SPECIFICATIONS	SIZE / QUANTITY
1.	LOWER FRAME (BOTTEM CHASSIS CHANEL)	MADE FROM 150 MM X 75 MMX 5 MM M.S. CHANEL AND 65 MM X65 MM X 5 MM ANGLE OF 4500 MM TO 4800 MM LENGTH.
2.	HEAVY FLY WHEEL WITH TOKA BLADE MODEL 1. 3 BLADES &	1.MADE FROM CAST IRON 700MM DIAMETER / 80KG. WT. / 65MM. THICK.
	2. 4 BLADES	2.MADE FROM CAST IRON 700MM DIAMETER/ 90KG. WT./ 65MM. THICK
3.	HEAVY BALANCE WHEEL	MADE FROM CAST IRON 1000MM DIAMETER/ 140KG. WT./ 100MM THICK

4.	THRESHING DRUM SIZE	812MM X 1168MM (OR) 900MMX 1200MM
5.	BEARING TYPES	TATA, SKF, NBC OR EQUIVALENTS.(TAPPER ROLLER BEARINGS & BALL BEARINGS)
6.	FANS SE	THERE IS PROVISION OF THREE TYPES OF FAN. 1. FIRST IS MAIN FAN (DISCHARGING FODDER). 2. SECOND IS CLEANING FAN (CLEANING GRAINS) 3. THIRD IS EXTRA CLEANING FAN.
7.	EXTRA SIEVES	3 NOS.
8.	EXTRA CONCAVE	3 NOS.
9.	FEEDER	CONVEYERED & BELT, UPPER FEEDING SYSTEM WITH REVERSE AND FORWARD GEAR CONTROL CONNECTED WITH 4.NOS. JOINTS.
10.	GEAR BOX	THERE IS PROVISION OF TWO FORWARD (SLOW AND FAST) & ONE REVERSE GEARS. EVEN THERE IS PROVISION OF FILLING OIL AND GREASING IN ALL THE ROTATING PARTS.
11.	JOINTS	4 NOS. JOINTS ARE ATTACHED WITH GEAR ASSEMBLY
12.	FITTING ACCESSORIES	ALL THE ACCESSORIES ARE FITTED WITH SUITABLE NUTS, BOLTS & WASHERS TO MAKE IT FOLDING.
13.	CAPACITY (DISCHARGING GRAIN)	20 TO 25 QUINTAL / HOUR
14.	P.T.O.(POWER TAKE OFF) R.P.M.	550 R.P.M.
15.	CUTTING BLADES	4. NOS CUTTING BLADES MADE FROM CARBON STEEL 2.5MM THICK. WHICH CAN BE ADJUSTABLE INTO 3 BLADES & 2 BLADES

16.	GRINDER -	1 NOS. GRINDER FITTED WITH MACHINE FOR SHARPING BLADES.
17.	TOOL BOX	A GOOD QUALITY WOODEN TOOL BOX ATTACHED WITH MACHINE. THIS IS USED TO CARRYING MACHINE ACCESSORIES.
18.	COUPLINGS FOR CONNECTING WITH TRACTOR PTO	A GOOD QUALITY COUPLING JOINT PROVIDED WITH MACHINE. WHICH CONNECTING TRACTOR TO THE MACHINE.
19.	SAFETY	ALL THE ROTATING PARTS ARE COVERED BY SAFETY GUARDS.
20.	THRESHER AVAILABLE IN EVERY TRACTOR MODEL	35 H.P. OR ABOVE CONNECT WITH TRACTOR
21.	OVER AII DIMENSIONS (A) LENGTH (B) WIDTH (C) HIGHT (D) WEIGHT	4500MM 1500MM 2200MM 2100KG. APPROX

FEATCHERS:-

- 1. IT CUT THE FODDER UNIFORMLY.
- 2. LOW LOAD ON TRACTOR DURING OPERATION.
- 3. TASTED BY EXPERIANCED ENGINEERS.
- 4. BEST PRODUCTION IN LESS TIME.
- 5. SUPERIOR QUALITY CUTTING BLADES FOR LONG SURVICE.
- 6. GOOD EFFICIENCY.

ADVANTAGES:-

- 1. DURABLE AND LONG LASTING.
- 2. FUNCTIONALLY SUPERIOR
- 3. LOW MAINTENANCE.
- 4. GOOD AVERAGE.

Note: - Designs, specifications, features and information are subject to change without any Notice.